

APPLIANCE LEAD WIRE

HERMETIC LEAD WIRE

Dacron/Mylar/Dacron braided insulation, compressor motor lead wire.

UL-5170 Bare Copper 125°C

Product	#CU/MFT	Stranding	Insulation	Min Order
5170-20-36-BC	3.37	42/36	DMD	25M
5170-20-30-BC	3.09	10/30	DMD	25M
5170-18-36-BC	5.00	65/36	DMD	25M
5170-18-30-BC	4.94	16/30	DMD	25M
5170-16-36-BC	8.09	61/0249	DMD	25M
5170-16-30-BC	8.03	26/30	DMD	25M
5170-14-36-BC	12.90	7X24/36	DMD	25M
5170-14-30-BC	12.66	41/30	DMD	25M
5170-12-36-BC	20.80	7X37/36	DMD	25M
5170-12-30-BC	20.80	65/30	DMD	25M
5170-10-36-BC	32.30	7X59/36	DMD	25M
5170-10-30-BC	32.50	105/30	DMD	25M
5170-8-36-BC	52.30	7X95/36	DMD	25M

UL-5170 Tinned Copper 125°C

Product	#CU/MFT	Stranding	Insulation	Min Order
5170-12-36-TC	20.80	7X37/36	DMD	25M
5170-10-36-TC	32.30	7X59/36	DMD	25M

UL-5058 Bare Copper 105°C

Dacron/Teflon/Mylar/Dacron braided insulation, compressor motor lead wire.

Product	#CU/MFT	Stranding	Insulation	Min Order
5084-14-36-BC	12.90	168/36	DTMD	25M
5084-12-36-BC	20.80	259/36	DMTD	25M
5084-10-36-BC	32.30	413/36	DTMD	25M
5084-8-36-BC	52.30	665/36	DMTD	25M

Minimum order requirement reflects quantity per color, per release.

800-776-9223 (Ohio)

800-684-7823 (Texas)