

APPLIANCE LEAD WIRE

LEAD WIRE

Polyvinyl chloride (PVC) insulated wire manufactured to UL and CSA standards.

APPLICATIONS:

Internal wiring of appliances.

UL-1007 Bare Copper 80°C 300 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1007-22-7-B	2.16	7/30	1/64	100M
1007-20-10-B	3.09	10/30	1/64	100M
1007-18-16-B	4.94	16/30	1/64	50M
1007-16-26-B	8.03	26/30	1/64	50M

UL-1007 Tinned Copper 80°C 300 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1007-22-7-T	2.16	7/30	1/64	100M
1007-20-10-T	3.09	10/30	1/64	100M
1007-18-16-T	4.94	16/30	1/64	50M
1007-16-26-T	8.03	26/30	1/64	50M

UL-1028 Bare Copper 105°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1028-18-16-B	4.94	16/30	3/64	50M
1028-16-26-B	8.03	26/30	3/64	50M

Minimum order requirement reflects quantity per color, per release. Different color quantities may be combined to determine pricing with solid colors treated separately from striped colors.

800-776-9223 (Ohio)

800-684-7823 (Texas)