

APPLIANCE LEAD WIRE

LEAD WIRE

Polyvinyl chloride (PVC) insulated wire manufactured to UL and CSA standards.

APPLICATIONS:

Internal wiring of electric refrigeration equipment, room air conditioners, room cooler units and remote outdoor condensing units for domestic cooling.

UL-1056 Bare Copper 105°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1056-18-16-B	4.94	16/30	4/64	50M
1056-16-26-B	8.03	26/30	4/64	50M
1056-14-41-B	12.66	41/30	4/64	50M

UL-1056 Tinned Copper 105°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1056-18-16-T	4.94	16/30	4/64	50M
1056-16-26-T	8.03	26/30	4/64	50M
1056-14-41-T	12.66	41/30	4/64	50M

APPLICATIONS:

Internal wiring of appliances where a heavy wall thickness is required.

UL-1060 Bare Copper 105°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1060-14-41-B	12.66	41/30	5/64	50M
1060-12-65-B	20.80	65/30	5/64	50M
1060-10-105-B	32.50	105/30	5/64	50M

UL-1060 Tinned Copper 105°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
1060-14-41-T	12.66	41/30	5/64	50M
1060-12-65-T	20.80	65/30	5/64	50M
1060-10-105-T	32.50	105/30	5/64	50M

Minimum order requirement reflects quantity per color, per release. Different color quantities may be combined to determine pricing with solid colors treated separately from striped colors.

800-776-9223 (Ohio)

800-684-7823 (Texas)