

# APPLIANCE LEAD WIRE

## LEAD WIRE

Crosslink polyethylene (XLPE) insulated wire manufactured to UL and CSA standards.

### APPLICATIONS:

Internal wiring of appliances.

### UL-3173,3195,3196 Bare Copper 125°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
3173-20-10-B	3.09	10/30	2/64	50M
3173-18-16-B	4.94	16/30	2/64	50M
3173-16-26-B	8.03	26/30	2/64	25M
3173-14-41-B	12.66	41/30	2/64	25M
3173-14-19-B	12.70	19/0147	2/64	75M
3173-12-65-B	20.80	65/30	2/64	25M
3173-12-19-B	20.15	19/0195	2/64	25M
3173-10-105-B	32.50	105/30	2/64	25M
3173-10-19-B	32.30	19/0234	2/64	25M
3195-8-133-B	53.10	133/29	3/64	25M
3196-6-133-B	82.20	133/27	4/64	25M
3196-4-133-B	130.00	133/25	4/64	25M

### UL-3173 7 Strand Bare Copper 125°C 600 Volts

Product	#CU/MFT	Stranding	Wall Thickness	Min Order
3173-18-7-B	5.04	7/0152	2/64	100M
3173-16-7-B	8.00	7/0192	2/64	100M
3173-14-7-B	12.76	7/0242	2/64	50M
3173-12-7-B	20.20	7/0305	2/64	50M
3173-10-7-B	31.72	7/0385	2/64	50M

Minimum order requirement reflects quantity per color, per release.

**800-776-9223 (Ohio)**

**800-684-7823 (Texas)**